

Product Data Sheet

PORTA POTTI 145



Product	Porta Potti 145
Positioning	The Porta Potti 145 fulfils the wishes of the low and mid end of the portable toilet market. The Porta Potti shows added value for the end users by the design, high quality and variation of product features. The position of this toilet is in the lower end of the mobile leisure market, often oriented on a temporarily use and domestic use of the toilet.
General USP's	The Porta Potti with its design includes the following added values (USP's) to sell the product: <ul style="list-style-type: none"> - Modern design - Improved valve handle system - Improved carry handle of the waste holding tank - Pour out spout stop - Integrated cover-lock - Improved seating comfort
Target group	<ul style="list-style-type: none"> - End users through sales in camping shops, hyper markets, DIY shops etc. - Dealers by promoting this portable toilet when selling a tent, folding caravan, a small/cheap caravan without a cassette toilet built-in or selling a second hand vehicle.
Flushing system	Manual flush: bellow pump
Flush water tank volume (L)	Porta Potti 145: 15 L
Average use of ml water when flushing the toilet	100 – 200 ml for urine, 150 – 300ml for faeces (average of 75 flushes before flush water tank is empty)
Waste-holding tank volume (L)	Porta Potti 145: 12 L
Flush water tank level indication	No
Waste-holding tank level indication	No
Outside measurements toilet (H x W x D, in mm)	PP 145: 330 x 383 x 427 mm (tolerance of +/- 5 mm)
Outside measurements waste holding tank (H x W x D, in mm)	PP 145 WHT: 185.5 x 383 x 427 mm (tolerance of +/- 5 mm)
Outside measurements flush water tank (H x W x D, in mm)	PP 145 FWT: 239.5 x 383 x 427 mm (tolerance of +/- 5 mm)
Seating Height (mm)	PP 145 : 324 mm
Maximum loading (kg)	120 kg (6000 cycles, official max. loading weight tests)

One time maximum load (kg)	400 kg. Mainly service parts e.g. pump can get damage but can be repaired. Furthermore mainly cosmetic issues (dented plastic parts which will normally dent out again).
Outside measurements packaging (H x W x D, in mm)	PP 145: 337 x 435 x 390 mm (tolerance of +/- 5 mm)
Contents Porta Potti	Toilet Instructions for use Additives flyer
Colour outercase	Full colour printed box
Temperatures	+1°C to +60°C (Operational) -40°C to +60°C (Storage)
Net weight toilet (kg) Gros weight toilet in outer case, manual, packaging material (kg)	Approx.: 3.6 kg Approx.: 4.5 kg
Possibility to upgrade bellow to piston pump?	Yes, piston pump available as spare part and installation instruction available on the website.
Quantity on pallet	PP 145: 36 pcs per pallet
Sales Quantity	No minimum sales quantity applicable
Available pictures	LR and HR images available on the website and Productmanagement directory
Countries available	Eastern Europe, Benelux, France, Germany, UK, Italy, Spain, Sweden, Denmark, Norway, Finland, International, USA & Canada
Availability	Delivery from TBV as from January 2018
Model	PP 145 White
Part number	92802
Ean-code	87 10315 024524
Designation	PP145-A111A007A

